



Rescue paths

Ensuring stability and safety in dangerous situations.

Rescue paths

Providing sure footing on all surfaces.

- › Ready for application in seconds
- › Flexibly expendable
- › Easy handling
- › Anti-slip surface

Always retain sure footing – even on unstable ground! With Vetter rescue paths, your team can walk safely across stretches of water, ice, moorland and bog. The rescue paths require very little compressed air and are ready to deploy in seconds. The three standard lengths of 6, 10 and 15 metres (19.2 ft., 32 ft. and 48 ft.) can be connected, so you will be prepared for any emergency scenario. The convenient anti-slip strips provide your team with a firm grip to safely rescue people who are drowning or sinking.



Safe walking on anti-slip strips.



Sure footing on the water surface.



Rescue path for emergency rescue at sea*

Technical data

Rescue paths with anti-slip strips	Ext. dimensions (L x W x H) cm / inch	Air requirement, at 0.5 bar (7.25 psi) litres / cu. ft.	Inflating time, approx. sec.	Folded size (L x W x H) cm / inch	Weight, approx. kg / lbs
6 m 1530008502	600 x 140 x 10 236 x 55 x 4	1,321 47	18	165 x 35 x 25 65 x 14 x 10	28.3 62.5
10 m 1530008602	1,000 x 140 x 10 394 x 55 x 4	2,196 78	30	165 x 45 x 25 65 x 18 x 10	45.4 100
15 m 1530008702	1,500 x 140 x 10 591 x 55 x 4	3,360 119	45	165 x 60 x 45 65 x 24 x 18	67.5 149

Rescue paths:
Working pressure: 0.5 bar (7.25 psi)
Test pressure: 0.65 bar (9.4 psi)

**Load capacity approx. 95 kg / m²
(2,255 lbs / sq. ft.)**

Accessories

Inflation hose, 500 mm (20 inch), for direct inflation from compressed air cylinder




1530003401
1530007600 (USA)
1530007100 (FR)

Compressed air cylinder

6 l / 300 bar, (0.21 cu. ft. / 4,350 psi) steel, 5/8" IT, 1,800 l (63.5 cu. ft.)

1600010800



9 l / 300 bar, (0.32 cu. ft. / 4,350 psi) composite, 5/8" IT, 2,700 l (95.3 cu. ft.)

1600019900

10 l / 200 bar, (0.35 cu. ft. / 2,900 psi) steel, 5/8" IT, 2,000 l (70.6 cu. ft.)

1600010500

Vacuum adapter for safety cushions and rescue paths

Attach quick action coupling to air source, the pressure should be between 4 and 6 bar (58 and 87 psi).



1600016300

**You need a special length?
No problem! Just let us know and we will produce it for you.**



In operation ...

- › Rescuing people who are drowning or who have fallen through ice
- › Rescue missions on unstable ground
- › Traversing stretches of water or boggy ground
- › Emergency sea rescue



Good reasons:

- › Inflated and ready to use in seconds
- › Several paths variably connectable
- › Optimum edge profile for pulling persons on board



Guaranteed quality:

- › Individually tested (with inspection seal)
- › Integrated safety valve prevents overinflation
- › Tear-proof material

